



Widest Point 50" (127cm)

Projection 3-3/4" 9.5cm

Made from

Arch-Polymer_{TM} Interior & Exterior. White Primed

Interior & Exterior, White Primed, High Quality, Cuts like Wood Similar density to White Pine, Rot, Water & Insect Resistant, Easy to Install

GRG (Glass Fiber Gypsum)

for Interior Use (minium order applies)

FRP (Fiberglass) for Exterior use (minium order applies)

* All specifications subject to change without notice, Measurements are approximate & Final Product may vary from this brochure



Imperial Productions® 1-800-399-7585 Imperial Productions & Distribution Inc Toronto / New York email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved



ArchPolymerTM is a high density rigid lite weight synthetic material with the same density as white pine. It is water, insect and rot resistant. All products are sold as decorative elements unless otherwise specified.

Measurements: All are represented as per manufacturing specifications. Final measurements may vary - Manufacturing Tolerances are +-1/8"

Trimming & Cutting: Like wood use a chop saw, table saw or jig saw

Health & Safety:

Always wear a mask and gloves when cutting, do not eat or ingest materials

Installation: Use only approved adhesive safe for polyurethane products Use screws or a brad nailer to affix to substrate

PAINTING / FINISHING: All products are white primed ready to paint

a) Factory Finish Painting: Available on select products only

b) DIY Painting: Do not use solvent based paints or install products close to areas with solvent based paints or adhesives. For exterior use to avoid UV degradation all products must be painted immediately upon installation with high quality exterior paint. Fill screw or brad nail holes with polyspackling compound prior to painting final coat. Do not use dark colors as they will increase UV degradation causing it to expand or contract at a higher rate.

FireRating: Standard Product does NOT meet Class A. Select products are offered with an Optional class A fire-rated foam mix. Third Party fire protectant can be applied which requires coating expert to verify thickness

Limited Manufacturer Warranty: One Year to original purchaser. Use of solvent based paints or adhesives voids warranty. Warranty resides with the respective

manufacturers - Imperial does not warranty products. RAN authorization # must be affixed to any product being returned to Imperial - There are no on site warranty claims.

* All specifications subject to change without notice, Final products & Measurements may vary from this brochure

