




Rams Head Pediment with Urn

IPPED811 ArchPolymer™

Martin Richards Design
COLLECTION


----- 62-1/8" (157.8cm) -----



----- 54" (127cm) -----


--- 3-3/4" ---
--- 9.5cm ---

21-9/16"
54.78cm



24-3/16"
61.44cm

*Suggest Use
with Pilasters
or Half Columns*



2-5/8"

|- 1-1/8" -|
|- 2.6cm -|

** assembly required, drawing not to scale*

* All specifications subject to change without notice, Final products & Measurements may vary from this brochure



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc New York / Toronto

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved



ArchPolymer™

Material Property Sheet

Apr-21

ArchPolymer™ is a high density rigid lite weight synthetic material with the same density as white pine. It is water, insect and rot resistant. All products are sold as decorative elements unless otherwise specified.

Measurements: All are represented as per manufacturing specifications.
Final measurements may vary - Manufacturing Tolerances are $\pm 1/8$ "

Trimming & Cutting: Like wood use a chop saw, table saw or jig saw

Health & Safety:

Always wear a mask and gloves when cutting, do not eat or ingest materials

Installation: Use only approved adhesive safe for polyurethane products
Use screws or a brad nailer to affix to substrate

PAINTING / FINISHING: All products are white primed ready to paint

a) Factory Finish Painting: Available on select products only

b) DIY Painting: Do not use solvent based paints or install products close to areas with solvent based paints or adhesives. For exterior use to avoid UV degradation all products must be painted immediately upon installation with high quality exterior paint. Fill screw or brad nail holes with polyspackling compound prior to painting final coat. Do not use dark colors as they will increase UV degradation causing it to expand or contract at a higher rate.

FireRating: Standard Product does NOT meet Class A. Select products are offered with an Optional class A fire-rated foam mix. Third Party fire protectant can be applied which requires coating expert to verify thickness

Limited Manufacturer Warranty: One Year to original purchaser. Use of solvent based paints or adhesives voids warranty. Warranty resides with the respective manufacturers - Imperial does not warranty products. RAN authorization # must be affixed to any product being returned to Imperial - There are no on site warranty claims.

* All specifications subject to change without notice, Final products & Measurements may vary from this brochure



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc New York / Toronto

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved